



FLEX CANVAS 370GSM

Product Description

FUJIFILM's Flex Canvas has been developed for industrial framed art and photo applications for best value. It is made of a cotton/polyester blend with a 1:1 wave. It's characterized by its high resistance to white scoring at 90°-180° angle, making it ideal for framed applications and use in automatic stretching machines.

Surface Single side coated with matt ink receptive coating

Weight 370 gsm

Caliper 515 micron

Opacity 93 %

Gloss (60°) < 5

Tint (Lab) 93.2/0.9/-0.5

Printer Compatibility

Compatible with most Photo-capable printers like Epson, Canon, HP Encad, etc.

Ink Compatibility

Aqueous pigment or dye* and HP latex

Handling Recommendations

Use gloves when handling media. Before finishing, allow approximately 24 hours to dry

Storage & Use Recommendations


Product should be stored under cool, dry conditions in its original packaging
 Temperature: 10-30°C
 Relative Humidity: 35-65%

Formats

SIZE	CORE	LENGTH	CAT NR.
610 mm (24")	2"	15 m	998933

* The use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

FUJIFILM's tips!

 Looking for a durable way to frame your canvases? Do not look any further and try our **Wunderbars framing systems!** The unique design of the bars, ensures that regardless of the hanging environment the canvases will remain under constant tension, eliminating sagging and rippling.