



IPP- F51GRAVURE 240

Product Description	FUJIFILM's Proofing media is a range of top quality proofing media meeting FOGRA standards												
Surface	Single side coated with satin ink receptive microporous coating												
Weight	257 gsm												
Caliper	255 micron												
Opacity	> 95 %												
Gloss (60°)	22												
Tint (Lab)	95.5, 0.7, -2.9 (M1) – 95.8, 0.3, -2.9 (M0)												
Printer Compatibility	Compatible with most Photo-capable printers like Epson, Canon, HP Encad, etc.												
Ink Compatibility	Aqueous pigment or dye*												
Handling Recommendations	Use gloves when handling media. Before finishing, allow approximately 24 hours to dry												
Storage & Use Recommendations	Product should be stored under cool, dry conditions in its original packaging Temperature: 10-30°C Relative Humidity: 30-65%												
Formats	<table border="1"> <thead> <tr> <th>SIZE</th> <th>CORE</th> <th>LENGTH</th> <th>CAT NR.</th> </tr> </thead> <tbody> <tr> <td>610 mm (24")</td> <td>3"</td> <td>45 m</td> <td>939741</td> </tr> <tr> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	SIZE	CORE	LENGTH	CAT NR.	610 mm (24")	3"	45 m	939741				
SIZE	CORE	LENGTH	CAT NR.										
610 mm (24")	3"	45 m	939741										

* The use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.