



## IPP-SG

<b>Product Description</b>	FUJIFILM's Proofing media is a range of top quality proofing media meeting FOGRA standards
<b>Surface</b>	Single side coated with matt ink receptive coating
<b>Weight</b>	235 gsm
<b>Caliper</b>	224 micron
<b>Opacity</b>	> 90 %
<b>Gloss (60°)</b>	22
<b>Tint (Lab)</b>	95.6, 0.2, -0.5
<b>Printer Compatibility</b>	Compatible with most Photo-capable printers like Epson, Canon, HP Encad, etc.
<b>Ink Compatibility</b>	Aqueous pigment or dye*
<b>Handling Recommendations</b>	Use gloves when handling media. Before finishing, allow approximately 24 hours to dry
<b>Storage &amp; Use Recommendations</b>	Product should be stored under cool, dry conditions in its original packaging Temperature: 10-30°C Relative Humidity: 20-70%
<b>Formats</b>	

SIZE	CORE	LENGTH	CAT NR.
A3+		100 SHEETS	939696
432 mm (17")	3" (2")**	30 m	939697
610 mm (24")	3" (2")**	30 m	939698
915 mm (36")	3" (2")**	30 m	939699
1067 mm (42")	3" (2")**	30 m	939700
1118 mm (44")	3" (2")**	30 m	939701
432 mm (17")	3" (2")**	45 m	939702
610 mm (24")	3" (2")**	45 m	939703

\* The use of aqueous dye ink will dramatically reduce image longevity. To determine longevity, testing in actual display conditions is required.

\*\* Delivered with a 2" core adaptor